



INSTALLATION INFORMATION AND RECOMMENDATIONS

General Instructions:

- **STORAGE:**
 - Paper products must be stored in an upright position in order to eliminate crush marks.
- **CAUTION**
 - Material must be examined prior to installation. No claims will be allowed for hanging the wrong color or pattern.
 - Wallcovering should be tested by hanging no more than three sheets.
 - No claims allowed for labor charges or consequential damages under any conditions.
 - Wallcoverings can display certain irregularities that are inherent to the manufacturing process.
 - Walls should be mirror smooth for optimum results.

Installation:

- **PRIMER:**
 - Tint the wallcovering primer to the color of the wallcovering.
- **ADHESIVE:**
 - Use a high quality heavy duty clear wallcovering adhesive.
- **TRIMMING:**
 - Paper Backed Papers should be trimmed on the table with a straight edge using a new razor blade for each cut.
- **RELAXING TIME:**
 - It is essential to allow wallcoverings sufficient relaxing time to avoid Bubbling, Shrinking and Seam Opening. Allow the paste enough time to soak into a sheet before hanging.
 - Usual Relaxing Time: 5 to 10 minutes.
 - Do a small test strip to determine the proper relaxing time.
- **HANGING:**
 - Care should be taken not to crease the wallcoverings.
 - The seams should be butted on the wall; do not overlap.
 - Care should be taken to trim all edges and excess with a very sharp blade to minimize fraying of the edges.

Avoid:

- Avoid soaking the paper in water or getting the wallcovering excessively wet. This can cause shrinkage and opening of seams as the wallcovering dries.
- Avoid adhesive from getting on the surface as it may stain.
- Avoid rubbing the face of the product with a stiff brush.
- Avoid pulling panels once they have been placed on the wall; this will cause the seams to open after the product dries.
- Avoid use of seam roller to set the seams.
- Avoid direct or bright reflected sunlight. Not guaranteed against fading or color change.

For best results, it is recommended that a qualified textile wall covering installer be employed