

■ Suburb Grade 1 or E
Upholstery Fabric



OLD CLARET
1BOT



MOLTEN
1BMN



SIERRA RIDGE
1BSE



OLD CLARET
1BOT



GOLDENROD
1BGD



BLUEPRINT
1BBT

■ Specification Information

Description	Suburb
Grade	1 or E
Content	60% Polyester, 40% Polypropylene
Repeat	4.5" Vertical, 4.5" Horizontal
Width	54"
Fabric Treatment	BLOCKaide™
Performance	
 Abrasion	Passes ASTM D4157-02 (ACT approved #10 Cotton Duck) 30,000 double rubs wire screen method. Abrasion resistance is the surface wear of a fabric caused by rubbing and contact with another fabric.
 Physical Properties	Passes Brush Pilling ASTM D3511-02, Class 3 minimum. Pilling is the formation of fuzzy balls of fiber on the surface of a fabric that remain attached to the fabric. Passes Breaking Strength ASTM D5034-95 (2001) (Grab Test). 50 lbs. minimum in warp and weft. Breaking strength is the measurement of stress exerted to pull a fabric apart under tension. Passes Seam Slippage ASTM D4034. 25 lbs. minimum in warp and weft. Seam slippage is the movement of yarns in a fabric that occurs when it is pulled apart at a seam.
 Colorfastness to Wet and Dry Crocking	Passes AATCC 8-2001 Dry Crocking, Grade 4 minimum. Wet Crocking, Grade 3 minimum. Crocking is the transfer of dye from the surface of a dyed or printed fabric onto another surface by rubbing.
 Colorfastness to Light	Passes AATCC 16 Option 1 or 3-2003 Grade 4 minimum at 40 hours. Colorfastness to light refers to a material's degree of resistance to the fading effect of light.
 Flame Resistance	Passes California Technical Bulletin #117 Section E – Class 1. Flame resistance is the measurement of a fabric's performance when it is exposed to specific sources of ignition.

Colors may vary slightly between dye lots. Suburb is a directional fabric. Pattern shown railroaded.

KI and Working For You
are registered trademarks of
Krueger International, Inc.

© 2007 KI Litho in USA KI-32371/HC/EWB/1007

